From-XEROX

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) An image module for a document scanner, the image module comprising:

a molded housing having a datum element;

an imaging sensor array <u>oriented for receiving an Image from a</u> <u>first direction</u>;

an array bias element urging the imaging sensor array in a second direction, different from the first direction, against the datum element; and a transport mechanism attached to the housing.

2. (Original) The image module of claim 1, wherein the housing comprises a unitary casting.



- 3. (Original) The image module of claim 2, wherein:
 the sensor array has opposed forward and rearward edges; and
 the array bias element comprises a spring clip abutting the
 rearward edge of the imaging sensor array to urge the forward edge of the
 imaging sensor array against the datum element.
- 4. (Currently Amended) The image module of claim 3, wherein:

 the datum element comprises a plurality of datum ribs; and the support element comprises a plurality of support ribs.

5. (Currently Amended) An image module for a	document
scanner, the image module comprising:	
a molded housing having a datum element;	
an imaging sensor array;	
an array bias element urging the imaging sensor array a	gainst the
datum element; and	•
a transport mechanism attached to the housing:	
wherein the housing comprises a unitary casting;	
wherein the sensor array has opposed forward and	rearward
edges;	
wherein the array bias element comprises a spring clip	abutting
the rearward edge of the imaging sensor array to urge the forward	d edge of
the imaging sensor array against the datum element; and	
The image module of claim 3, wherein the imaging sen	ısor array
comprises a board having a front surface and a back surface, and	a plurality
of sensor elements on the front surface of the board.	

- 6. (Original) The image module of **claim 5**, wherein the board comprises plural boards, each having a front surface and a back surface.
- 7. (Original) The image module of claim 6, wherein the plural boards are attached to one another.
- 8. (Original) The image module of **claim 7**, additionally comprising a resilient seal and a bottom cover attached to the housing.
- 9. (Original) The image module of **claim 8**, wherein the document transport mechanism comprises a drive shaft and a paper contact device.
- 10. (Original) The image module of **claim 1**, additionally comprising:
- a lens attached to the housing above the sensor elements of the imaging sensor array;
- a light filter in the light path between the lens and the imaging sensors of the imaging sensor array; and
 - a lamp attached to the housing.



From-XEROX

- 11. (Original) A document scanner comprising:
- a housing having a datum element and a support element;
- an imaging sensor array comprising:
- a sensor board having a forward edge and a rearward edge, and a front surface and a back surface, wherein the front surface of the sensor board abuts the support element; and
- a plurality of sensor elements on the front surface of the sensor board;
- a spring clip abutting the rearward edge of the imaging sensor array to urge the forward edge of the imaging sensor array against the datum element:
- a lens attached to the housing above the sensor elements of the imaging sensor array;
 - a lamp mounting on the housing; and
- a transport mechanism attached to the housing, wherein the transport mechanism moves the housing and a document relative to one another.
 - 12. (Original) The scanner of claim 11, wherein: the datum element comprises a plurality of datum ribs; and the support element comprises a plurality of support ribs.
- 13. (Original) The scanner of **claim 11**, wherein the housing additionally includes a side reference element, and the scanner additionally comprises a lateral spring for urging an edge of the sensor board against the reference edge.



- 14. (Original) The scanner of claim 13, wherein the sensor board includes first and second opposed side edges between the forward and rearward edges, and the lateral spring abuts the first side edge to urge the second side edge against the side reference element.
- 15. (Original) The scanner of claim 11, wherein the transport mechanism is a document transport mechanism for moving the document relative to the housing.
- 16. (Currently Amended) A method of assembling a document scanner, the method comprising:

providing a housing having a support element and a datum element:

placing an imaging sensor array on the support surface of the housing so that the imaging sensor array is oriented to receive images from a first direction;

urging the imaging sensor array in a second direction, different from the first direction, against the datum element;

attaching a document transport mechanism to the housing; and attaching a bottom cover to the housing to enclose the imaging sensor array.

17. (Original) The method of **claim 16**, additionally comprising: attaching a lens to the housing; and attaching a lamp to the housing.



	18. (Currently Amended) A method of assembling a document
scanner, 1	the method comprising;
	providing a housing having a support element and a datum
<u>element;</u>	
 -	placing an imaging sensor array on the support surface of the
housing:	
	urging the imaging sensor array against the datum element;
	attaching a document transport mechanism to the housing:
V	attaching a bottom cover to the housing to enclose the imaging
sensor ar	ray; and
	_ The method of claim 17, additionally comprising enclosing a
resilient s	eal between the imaging sensor array and the bottom cover.
	19. (Currently amended) A method of assembling a document
scanner, t	he method comprising:
	providing a housing having a support element and a datum
element;	
	placing an imaging sensor array on the support surface of the
housing;	
	urging the imaging sensor array against the datum element;
	attaching a document transport mechanism to the housing; and
•	attaching a bottom cover to the housing to enclose the imaging
sensor arı	<u>av:</u>

array against the reference element.

reference element substantially perpendicular to the datum element, and the method additionally comprises urging a second edge of the imaging sensor

The method of claim 16, wherein the housing additionally has a

From-XEROX

٤٠٦

- 20. (New) The image module of **claim 1**, wherein the second direction is substantially perpendicular to the first direction.
- 21. (New) The method of claim 16, wherein the second direction is substantially perpendicular to the first direction.